

LX7-3000 WHEEL ALIGNER LASER



Company Name MAFFRA STREET COOLAROO VICTORIA 3046		Telephone: 123456 Facsimile: 03 9309 0069 E-Mail: oem@oem.com.au																																																																																																	
LX7-3000 LASER WHEEL ALIGNER		CUSTOMER: JOHN SMITH																																																																																																	
MAKE: FORD	TYPE: BF XR Sedan 370 mm Rise Height	REG No: ABC 123	KM Reading:																																																																																																
MODEL: FALCON	YEAR: 2005-06	VEHICLE CHECKS: <input checked="" type="checkbox"/> Wheel Bearings <input checked="" type="checkbox"/> Steering Box / Rack <input checked="" type="checkbox"/> Rod Joints <input checked="" type="checkbox"/> Suspension <input checked="" type="checkbox"/> Tyre Pressure <input checked="" type="checkbox"/> Shock Absorbers																																																																																																	
<table border="1"> <thead> <tr> <th rowspan="2">MANUFACTURER'S SPECIFICATION</th> <th rowspan="2">Spec</th> <th rowspan="2">H-</th> <th colspan="2">Actual Settings (LH)</th> <th colspan="2">Total Top</th> <th colspan="2">Actual Settings (RH)</th> </tr> <tr> <th>Before</th> <th>After</th> <th>Before</th> <th>After</th> <th>Before</th> <th>After</th> </tr> </thead> <tbody> <tr> <td>Front Toe-in (mm)</td> <td>2</td> <td>1</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Front Camber (deg)</td> <td>-0.21</td> <td>5</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Front Caster (deg)</td> <td>7.49</td> <td>5</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>SAI (deg)</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>TOOT Inside (deg)</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>TOOT Outside (deg)</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Set Back (mm)</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Rear Camber (deg)</td> <td>-1.10</td> <td>25</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Rear Toe-in (mm)</td> <td>2</td> <td>1</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>		MANUFACTURER'S SPECIFICATION	Spec	H-	Actual Settings (LH)		Total Top		Actual Settings (RH)		Before	After	Before	After	Before	After	Front Toe-in (mm)	2	1							Front Camber (deg)	-0.21	5							Front Caster (deg)	7.49	5							SAI (deg)									TOOT Inside (deg)									TOOT Outside (deg)									Set Back (mm)									Rear Camber (deg)	-1.10	25							Rear Toe-in (mm)	2	1							<p>IMPORTANT INFORMATION Specifications are to be used ONLY with the Servex LX7-3000 Laser Aligner.</p> <p>All Toe-In Specifications are based on a linear measurement taken at the tyre edge.</p> <p>LX7-3000</p>	
MANUFACTURER'S SPECIFICATION	Spec				H-	Actual Settings (LH)		Total Top		Actual Settings (RH)																																																																																									
		Before	After	Before		After	Before	After																																																																																											
Front Toe-in (mm)	2	1																																																																																																	
Front Camber (deg)	-0.21	5																																																																																																	
Front Caster (deg)	7.49	5																																																																																																	
SAI (deg)																																																																																																			
TOOT Inside (deg)																																																																																																			
TOOT Outside (deg)																																																																																																			
Set Back (mm)																																																																																																			
Rear Camber (deg)	-1.10	25																																																																																																	
Rear Toe-in (mm)	2	1																																																																																																	
User Name:	OPERATOR: jim	DATE: 18/09/2006	SIGNATURE:																																																																																																
	JOB No: 123																																																																																																		

- 4 LASER READINGS
- CD OF VEHICLE SPECIFICATIONS
- QUICK ACTING WHEEL CLAMPS
Fit up to 20" Rims - Standard
Fit up to 24" Rims - Optional Kit
- CAMBER, CASTER, SAI TOOT & SET BACK

SERVEX EQUIPMENT